




- Precision controlled refrigeration system designed for quality product consistency from the first cone to the last.
- Hard-working, compact counter-top unit that can handle peak demands, while providing years of dependable service.
- E111 is the highest capacity 115 volt soft serve freezer available (reduces installation costs).
- IntelliTec[™] control communicates with the operator for worry-free operation.
- Energy Conservation Mode (ECM) protects product from over-agitation during slow or non-draw periods.
- Proprietary auger design gently folds mix and prevents product breakdown, producing a smoother, creamier product.
- Clear door shows visible moving product for merchandising appeal.
- Self-closing spigot eliminates waste and ensures precise portion control.
- Adjustable dispense rate for optimal product output.
- Long-wearing parts offer lower preventative maintenance costs.
- Built for ease of operation and cleaning.
- Optional floor stand to create a "floor model" package, freeing up counter space and providing additional storage.







Model E111I		Model F111I	
Machine	with crate	Machine	with crate
15-1/8" (38,4 cm)	19-1/2" (49,5 cm)	15-1/8" (38,4 cm)	19-1/2" (49,5 cm)
35-5/8" (90,5 cm)	43" (109,2 cm)	35-5/8" (90,5 cm)	43" (109,2 cm)
28-7/8" (73,3 cm)	33-1/2" (85,1 cm)	28-7/8" (73,3 cm)	33-1/2" (85,1 cm)
220 lbs (99,7 kg)	265 lbs (120,2 kg)	230 lbs (104,3 kg)	275 lbs (124,7 kg)
1 Phase, 115 VAC, 60Hz		1 Phase, 208-240 VAC, 60Hz	
14A		8A	
NEMA5-20P power cord provided		NEMA6-15P power cord provided	
1 Phase, 220-240 VAC, 50Hz		1 Phase, 220-240 VAC, 50Hz	
3,550 Btu/hr		5,450 Btu/hr	
3/4 hp			
Air cooled units require 3" (7,6 cm) air space on both sides			
N	/A	Water cooled units require 3/8" N.P.T.	
		water and drain fittings.	
3 gallon (11,35 liters)			
0.65 gallon (2,46 liters)		0.85 gallon (3,22 liters)	
	Machine 15-1/8" (38,4 cm) 35-5/8" (90,5 cm) 28-7/8" (73,3 cm) 220 lbs (99,7 kg) 1 Phase, 114 NEMA5-20P pow 1 Phase, 220-2 3,550 Air coole	Machine with crate 15-1/8" (38,4 cm) 19-1/2" (49,5 cm) 35-5/8" (90,5 cm) 43" (109,2 cm) 28-7/8" (73,3 cm) 33-1/2" (85,1 cm) 220 lbs (99,7 kg) 265 lbs (120,2 kg) 1 Phase, 115 VAC, 60Hz 14A NEMA5-20P power cord provided 1 Phase, 220-240 VAC, 50Hz 3,550 Btu/hr 3/4 Air cooled units require 3" (7, N/A) 3 gallon (1	Machine with crate Machine 15-1/8" (38,4 cm) 19-1/2" (49,5 cm) 15-1/8" (38,4 cm) 35-5/8" (90,5 cm) 43" (109,2 cm) 35-5/8" (90,5 cm) 28-7/8" (73,3 cm) 33-1/2" (85,1 cm) 28-7/8" (73,3 cm) 220 lbs (99,7 kg) 265 lbs (120,2 kg) 230 lbs (104,3 kg) 1 Phase, 115 VAC, 60Hz 1 Phase, 208-2 14A 8 NEMA5-20P power cord provided NEMA6-15P power 1 Phase, 220-240 VAC, 50Hz 1 Phase, 220-2 3,550 Btu/hr 5,450 3/4 hp Water cooled units water and of the wat

Continuous research leads to ongoing product improvements; therefore, these specifications are subject to change without notice and should not be used as installation specifications.

^{*} Machine requires a dedicated electrical circuit.





FOODSERVICE EQUIPMENT

502 Highway 67 • Kiel, WI 53042-1600 920-894-2293 • 800-558-5807

Fax: 920-894-7029

E-mail: foodservice@stoelting.com www.stoeltingfoodservice.com ISO 9001:2008 Registered

Certified, Listed and/or Recognized by:





STMF-106 04/12