CHEESE TABLES

Cheese table, type SM

Basic cheese table on a stable support with an edge of 40 mm Material: stainless steel AISI 304



Туре
SM-97
SM-147
SM-199
SM-249
SM-299

Additional equipment:

- deposit shelf under the table
- draining grid under the table
- support on wheels

Cheese table - heated, type SMG

Cheese table on a stable support with a **heated working plane**. Connection to water supply. With this system we prevent the sudden cooling of the cheese grain when it comes in contact with the cold surface of stainless steel.

Material: Stainless steel AISI 304



Type SMG-97 SMG-147 SMG-199 SMG-249 SMG-299

Additional equipment:

- deposit shelf under the table
- draining grid under the table
- support on wheels



PLEVNIK production and marketing d.o.o. Podsmreka 56, 1356 Dobrova, Slovenia Tel.: 00386 / (0)1 200 60 80 Fax.: 00386 / (0)1 257 44 22

E-mail.: info@plevnik.si, http://www.plevnik.si

REPRESENTATIVE

Cheese model table, type SDM

It is used for the direct filling of cheese models by pouring cheese curd and whey into the table.

Material: stainless steel AISI 304

Composition: deepened cheese table, support on wheels, outflow valve for whey, basic dividing plate with a 100 mm edge (for cheese up to 3 kg)



E M	
Туре	Processing capacity (kg)
SDM-1010	cca. 40
SDM-1510	cca. 70
SDM-2010	cca. 90

cca. 120

cca. 140

Additional equipment:

- deposit shelf under the table
- draining grid under the table
- draining perforated grid at the bottom of the table
- extra dividing plate (for a different size of cheese)

Table depth: 200 mm

SDM-2510

SDM-3010

The dividing plate Ø180 mm is suitable for cheese models with an outside diameter up to 240 mm (cheese of cca. 3 kg). The dividing plate Ø140 mm is suitable for cheese models with an outside diameter up to 195 mm (cheese of cca. 2 kg).

Cheese draining table, type SOM

The cheese draining table is used for the draining of cheese curd into a single cheese block. The cheese curd with whey is poured in the place bounded by two draining grids (the distance between the grinds can be adjusted regarding to the quantity of curd). After the draining the cheese block is manually cut into smaller pieces that will be putted in cheese forms.

Material: AISI 304

Composition: deepened cheese table, support on wheels, side draining grids, outflow valve



Туре	Processing capacity (kg)
SOM-109	cca. 60
SOM-159	cca. 90
SOM-209	cca. 120
SOM-2510	cca. 150
SOM-3010	cca. 190

Table depth: 350 mm

Additional equipment :

- deposit shelf under the table
- draining grid under the table
- draining stainless steel grid at the bottom of the table

DIFLINING
PLFYNIK

PLEVNIK production and marketing d.o.o. Podsmreka 56, 1356 Dobrova, Slovenia Tel.: 00386 / (0)1 200 60 80

Fax.: 00386 / (0)1 257 44 22

E-mail.: info@plevnik.si, http://www.plevnik.si

REPRESENTATIVE